

PMR04

Bourdon Tube Pressure Gauge

- nominal sizes 100, 160 and 250 mm
- accuracy class 1,0
- designs with brass connection and stainless steel housing or completely in stainless steel
- with or without liquid filling for vibration dampening
- optional up to 4 magnetic snap-action contacts or inductive contacts
-  Ex- version acc. to ATEX optional
- measuring range from -1000...0 mbar to 0...1600 bar



Description:

Model series PMR04 Bourdon tube pressure gauges can be supplied in brass or stainless steel versions, with filled or unfilled gauges. A coiled, drawn brass or stainless steel tube filled with the fluid or gas being monitored is deformed to an extent depending on the pressure exerted by the fluid or gas. The resulting movement of the coil is transmitted to an indicator mechanism with a graduated display. This movement can be dampened by means of an optionally available liquid filling so that any vibrations have far less impact on the accuracy and stability of the reading. The natural lubricating properties of this liquid filling also reduce wear to moving parts, entry of caustic/corrosive gases and accumulation of condensation. The stainless steel version allows pressure measurement of even the most caustic liquids and gases. These pressure gauges are fitted with a threaded connection at the bottom or on the back. They may also be fitted with up to four limit contacts or with a transmitter for remote transmission of the measured value.

Typical applications:







Bourdon tube gauges are used throughout industry and are especially suitable for taking measurements at locations where there is no supply of electrical power available. Model PMR04 Bourdon tube pressure gauges, with a brass responsive element, are frequently used in industrial machinery and systems, on pumps, compressors, or block-type thermal power stations (BTTPs) since in these applications they only need to meet minimal requirements for withstanding the effects of the media being monitored.

In contrast, PMR04 Bourdon tube pressure gauges of stainless steel are designed to withstand contact with the very caustic/corrosive media often encountered in the chemical and petrochemical industries, the food and beverage industries, pharmaceutical production processes or in power plants, where they have provided the best service for decades. When fitted with the optionally available switching contacts or analogue output, these gauges can also be used for electronic pressure monitoring.

Models:

Nominal sizes:	housing diameters 100, 160 or 250 mm
Materials:	
PMR04.M:	housing of st. steel 1.4301, measuring element of copper alloy, above 100 bar st. steel, connection of Messing
PMR04.E:	housing of st. steel 1.4301, measuring element and connection of stainless steel 1.4571
Process connection:	G 1/2 or 1/2" NPT at bottom or on back
Vibration dampening:	optional glycerine-, oil- or special filling

Measuring ranges:

Measuring-range [bar]	Order number					
						
	for all nominal sizes					not for NG 250
-1000...0 mbar	A17	B17	C17	D17	E17	F17
-1...0	A16	B16	C16	D16	E16	F16
-0,6...+1,0	A18	B18	C18	D18	E18	F18
-1...+0,6	A42	B42	C42	D42	E42	F42
-1...+1,5	A43	B43	C43	D43	E43	F43
-1...+3	A44	B44	C44	D44	E44	F44
-1...+5	A45	B45	C45	D45	E45	F45
-1...+9	A46	B46	C46	D46	E46	F46
-1...+15	A49	B49	C49	D49	E49	F49
0,2...1	A50	B50	C50	D50	E50	F50
0...0,6	A67	B67	C67	D67	E67	F67
0...1	A69	B69	C69	D69	E69	F69
0...1,6	A70	B70	C70	D70	E70	F70
0...2,5	A72	B72	C72	D72	E72	F72
0...4	A73	B73	C73	D73	E73	F73
0...6	A74	B74	C74	D74	E74	F74
0...10	A75	B75	C75	D75	E75	F75
0...16	A76	B76	C76	D76	E76	F76
0...25	A78	B78	C78	D78	E78	F78
0...40	A79	B79	C79	D79	E79	F79
0...60	A80	B80	C80	D80	E80	F80
0...100	A81	B81	C81	D81	E81	F81
0...160	A82	B82	C82	D82	E82	F82
0...250	A84	B84	C84	D84	E84	F84
0...400	A86	B86	C86	D86	E86	F86
0...600	A87	B87	C87	D87	E87	F87
0...1000	A88	B88	C88	D88	E88	F88
0...1600	A89	B89	C89	D89	E89	F89

Order Code:

Order number: **PMR04. 10. M. 1. 0. A75. 0. 0**

Bourdon tube pressure gauge

Models:

10 = 100 mm
16 = 160 mm
25 = 250 mm

Materials:

M = housing st. steel, connection brass
E = housing st. steel, connection st. steel
S = special material, (please specify in plain text)

Process connection:

1 = G 1/2 at bottom
2 = G 1/2 eccentric on back (not with contact)
3 = 1/2" NPT at bottom
4 = 1/2" NPT eccentric on back (not with contact)
8 = with adapter for connection of a diaphragm seal
9 = special connection

Vibration dampening:

0 = without
1 = with glycerine filling
2 = with oil filling (for devices with contact)

Design and measuring ranges:

A17...F89 = see table „Measuring ranges“

Optional electrical devices:

0 = without
xxx = see table „Limit contacts“

Options and accessories (multiple selection possible):

0 = without
xx = see table „Options and accessories“

Technical Data:

Housing:

round gauge of stainless steel,
d = 100 mm, 160 or 250 mm
protection class IP45

Liquid filled design:

glycerine filling, (optional other filling), with pressure relief opening and inside-pressure, protection class IP65

Stainless steel version:

with pressure relief opening (optional for increased safety with solid baffle wall and blow-out back)

Measuring element:

PMR04.xx.M: bourdon, bis 60 bar copper alloy, soldered, ab 100 bar st. steel 1.4571, brazed
PMR04.xx.E: bourdon tube of stainless steel 1.4571

Indicator element:

PMR04.xx.M: brass, moving parts of nickel silver
PMR04.xx.E: stainless steel 1.4571 / 1.4301

Dial face:

aluminium, white, black characters
acc. to EN 837-1

Viewing window:

PMR04.xx.M: instrument glass
PMR04.25.M.x.1/2 Polycarbonate
PMR04.xx.E: multilayer safety glass

Accuracy:

class 1,0

max. medium temperature:

PMR04.xx.M: bis 40 bar: 80 °C (60 °C with glycerine filling)
ab 60 bar: 120 °C (100 °C with glycerine filling)
PMR04.xx.E: 200 °C (100 °C with glycerine filling)

Overload protection:

short-term 1,3-times

Limit contacts:

Designs:

magnetic spring contact

as N/O contact, N/C contact (max. 4 units.)
or SPDT (max. 2 units.)
switching capacity: max. 30 W / 50 VA
switching voltage: 24...250 V

inductive contact

as N/O contact or N/C contact (max. 4 units.)
nominal voltage: 8 VDC
power consumption:
high: >3 mA, low: <1 mA
optional with Ex-certification gem. ATEX
for use in zone 1 or 2

Other contacts designs such as slow action contacts or electronic contacts for direct connection to a SPS on request (for model A, B, and C only).


Description: (contact operation with pointer movement in the clockwise direction)	Code: 1 = N/O 2 = N/C 3 = SPDT
1 magnetic spring contact, N/O	M1
1 magnetic spring contact, N/C	M2
1 magnetic spring contact, SPDT	M3
2 magnetic spring contacts, switching function x = N/C, N/O or SPDT	Mxx
3 magnetic spring contacts, switching function x = N/C or N/O	Mxxx
4 magnetic spring contacts, switching function x = N/C or N/O	Mxxxx
1 inductive contact, N/O	I1
1 inductive contact, N/C	I2
2 inductive contacts, switching function x = inductive contact	Ixx
3 inductive contacts, switching function x = inductive contact	Ixxx
4 inductive contacts, switching function x = inductive contact	Ixxxx

Advice: For the use of additional electrical equipment in fluid filled devices instead of the glycerine filling an oil filling must be used


Options and accessories:

Description:	Code	for model PMR04
design for increased safety (solid baffle wall and blow-out back)	ES	x.E..., unfilled, not for NG 250, designs A, B only
protective cap of blue rubber	GB	10.M... designs A, D
bright metal bezel	FP	x.E... designs B, E, F
housing suitable for tropical climate	GT	unfilled devices only
indicator element of stainless steel	ZE	x.M... unfilled
indicator element dampened	ZD	unfilled devices only
scale with fine graduations and knife edge pointer	SFS	all models
double-scale (e.g. bar / psi)	SD	all models
multiple scale	SM	all models
scale labeling	SA	all models
refrigerant double-scale dial pressure / R22, R134a, R507 pressure / R22, R12, R502 pressure / R12 pressure / R22 pressure / R507 pressure / R134a	SK... ...1 ...2 ...3 ...4 ...5 ...6	x.M.
refrigerant double-scale dial pressure / R717 (NH3)	SK7	x.E...
print plate for creating special scale (single color or multi-colored)	SS1 SSx	all models
multilayer safety glass	WS	x.M..., unfilled
measuring system free of oil and grease for use with oxygen	MO	all models
measuring system free of silicone	MS	all models
silicone oil filled	FS	x.E..., filled, and with option ES (increased safety)
glycerine filled	FG	only with Option ES (increased safety)
measuring system with excess pressure protection > 1,3 times	U	all models
pressure throttling screw in the connection, d = 0,8 or 0,3 mm	D08 D03	all models
process connection G 1/4 B, 1/4" NPT, 7/16"-20 UNF	Px	all models, nt for NG 250
process connection G 1/4 female, G 3/8 B, 3/8" NPT, M20 x 1,5, small flange DN10, st. steel	Px	all models
process connection M16x1,5 female thread	Px	x.E...
yellow graduations on dial face for N2 or blue graduations on dial face for O2	MG MB	x.M..., unfilled, not for NG 250
red graduations on dial face	MR	all models
red gliding mark pointer in the viewing window	ZR	all models
red gliding mark pointer on the dial face, 1 time or 2 times	ZR1 ZR2	unfilled devices only
maximum pointer can be reset, 1 time or 2 times	ZS1 ZS2	all models
adjustable pointer on bushing	ZZ	all models
can be calibrated as per calibration regulations	E	all models
press. sensor integrated in back of housing	PU	x.E..., unfilled


Models:




model A:
connection at bottom




model B:
connection at bottom,
rim at front




model C:
connection at bottom,
rim at back



model D:
connection on back



model E:
connection on back,
rim at front
panel cut-out:
NG 100: 105 mm
NG 160: 165 mm
NG 250: 254 mm



model F:
connection on back
triangular front ring and
retaining clip
panel cut-out:
NG 100: 103 mm
NG 160: 163 mm
NG 250: /

Standard version:

Dimensions:	Value [mm]		
	NG 100	NG 160	NG 250
b	50	50	55
b1	56	56	61
b2	86,5	88	93
c	15	14,5	16
c1	29	50	50
D	100,8	161,3	251
d1	116	178	271
d2	132	196	285
d3	4,8	5,8	5,8
d4	107	166	-
h	87	118	165
SW	22	22	22
weight [kg]	0,5	1,1	2,2